

**TOWN OF DOVER, VERMONT
2019 PAVING AND RECLAMATION BIDS**

BID & SPECIFICATIONS

The contractor shall do full-depth reclamation work and mixing existing asphalt pavement and base . All hot mix shall meet State of Vermont DOT latest specifications. There will be no more than 10% recycled asphalt and no asphalt shingles in the mix All shim and overlay will have tack. All overlay's to have 70-28 grade binder. Shim and base asphalt mix to have 58-28.

1. The contractors shall reclaim and pave the following roads:

Name of Road	Length X Width	
North Street	7400 ft. x 22 ft.	Reclaim _____
Lower Highlands	1300 ft. x 22 ft.	Reclaim _____
Upper Handle	1400 ft. x 22 ft.	Reclaim _____
Jockey Hollow	1200 ft. x 22 ft.	Reclaim _____
Dover Hill Road	5280 ft. x 24 ft.	Pave _____
Valley View	8000 ft. x 22 ft.	Pave _____

Price for a complete reclamation work (Not including paving):	\$ _____
Cost per Square Yard:	\$ _____
Additional: Emulsified Asphalt (Delivered)as per job mix formula	\$ _____
Price per gallon	\$ _____
Price per ton for paving	\$ _____

2. Contractor shall do Full Depth Reclamation with Emulsion Injection .
At a rate of 4 gallons per square yard at 4" depth
3. All material shall conform to the following gradation:

Sieve Size: Road material must be ground 2" or less 98-100%. If the largest aggregate in the road is smaller than 2" the maximum number of passes allowed is two (2). For depths over 8" the maximum number of passes is four (4). If deemed necessary, virgin material may be added by the Town. The Town will supply the material and grader.

4. The Road Commissioner will mark all roads before work begins.

5. The Contractor will provide the grader. The contractor will provide rollers, signs and all traffic control.
6. For pavement work, the pavement shall be 24 or 22-feet wide and no less than 2-inches of 3/4" stone base pavement with an overlay of 1-inch of 3/8" hot mix for a total of 3". For shim and overlay 2" of pavement total
7. All driveways will have a 2-foot apron. All intersecting roads must make a smooth transition both off and on roads.
8. The contractor must sweep all shimming and overlay work. The materials used for shim and overlay will be 3/8 to 1/2 inch stone.
9. The contractor must use two rollers when paving
10. Equipment used by the contractor must be approved by the Road Commissioner and maintained in satisfactory working condition at all times.
11. Bid prices may change depending on work being completed.
12. Bids must be sealed and in by May 24, 2019 at the Dover Town Office, to be awarded June 4, 2019 at the regular Select board meeting.
13. The Town Point of Contact is Commissioner Bob Holland. Call (802) 464-2000 for more information or questions. Bidders are expected to meet with Mr. Holland. Call to arrange meeting times.
14. All work must be completed by September 4, 2019. The contractor will be assessed \$500.00 per day penalty for each calendar day after that until completed.
15. Bid prices per ton can't change after the bid has been awarded.

Town of Dover
Attn: Paving Bid
P.O. Box 428
West Dover, VT 05356

Or, hand-deliver to Dover Town Office, 102 Route 100, West Dover, VT 05356

IMPORTANT

THE TOWN OF DOVER RESERVES THE RIGHT TO ACCEPT OR REJECT ALL BIDS IN THE BEST INTEREST OF THE TOWN. ONCE WE RECEIVE BIDS, CONTRACTORS ARE NOT ALLOW WITHDRAW THEIR PROPOSALS FOR A PERIOD OF 30-DAYS, UNLESS RELEASED BY THE TOWN.